

DIEBOLD SECURITY

# ACCUTRACK ELITE 3200 DVR

For a customizable security solution, choose the Diebold AccuTrack Elite 3200 digital video recorder (DVR).



## Benefits:

- AccuTrack Elite 3200 comes in configurations of 4, 8, 16 and 32 video inputs, which includes an increased number of video outputs, alarm inputs and alarm outputs. The combination of these components makes the unit virtually customizable to the user's surveillance needs.
- AccuTrack Elite 3200 is now a Windows XP-based system. This robust operating system does true multi-tasking.
- Multiple storage solutions available from 500 gigabytes, expandable to 2000 gigabytes (2 terabytes).
- For ATM monitoring, transaction data is stored in addition to video images. Enter any transaction ID number and AccuTrack instantly presents the data and related video images.
- AccuTrack instantly detects when power has been restored after a site power failure. The unit will restart automatically without the need for operator intervention.
- Connects to any network that uses TCP/IP using either a Token-Ring or Ethernet card.

**DIEBOLD**<sup>®</sup>

## AccuTrack Elite 3200 Features

AccuTrack Elite 3200 is a Windows XP-based system. This robust operating system allows the software to run many different programs simultaneously, while multiple operators can log-on from different locations simultaneously, without overburdening the system.

The unit comes in configurations of 4, 8, 16 and 32 video inputs. These configurations include an increased number of video outputs (4), alarm inputs (up to 32) and alarm outputs (up to 8). This can be expanded as the user's surveillance needs increase.

In addition to performing search by time/date, camera number and alarm type; an operator can search for images relating to ATM transactions by entering detailed transaction data. For instance, an operator can enter the unique transaction ID number to quickly find images and data relating to a specific ATM transaction.

A fully-loaded system can be configured to capture images at up to 64 frames per second (fps), enabling images to be captured from all 32 cameras in less than one second. In addition, image capture can be optimized by configuring the system to capture images only when an event occurs, such as a holdup, or if motion is detected.

Users can program AccuTrack Elite 3200 to automatically increase capture rate for the system during specified events. AccuTrack has built-in motion detection support for all video inputs. When motion is detected at any camera, the frame rate for the camera can be increased to any user-defined speed. AccuTrack can also be configured to a higher image resolution of 640 x480 to capture the highest quality images possible, greatly improving the ability to identify details and individuals during an investigation.

AccuTrack Elite 3200 offers multiple storage solutions from 500 gigabytes, expandable to 2000 gigabytes (2 terabyte). That much storage puts millions of video images at your fingertips during the investigation of fraud, burglary, vandalism or other events.

All storage solutions are contained in lockable cartridges easily accessed from outside the unit. Drives can be "hot-swapped" during maintenance or replacement with no interruption to system operation or image capture.

With AccuTrack Elite 3200's RAID option, a failed drive doesn't mean lost data. RAID redundancy reduces data loss risk. Recorded data is spread across multiple drives, so if a drive fails the system automatically rebuilds images from redundant data on the other drives.

## AccuTrack Elite 3200 Specifications

Alarm Input Type (maximum of 32):	Continuity
Alarm Input Cable Length:	2000 ft.
Output Relay Contacts (maximum of 8):	1 amp. 30 VAC/VDC
Video Inputs:	32
Video Outputs:	4
Video Level:	1.0 V peak to peak
Video Type:	NISC/PAL
Video Input Connector Type:	BNC
AccuTrack Elite 3200 Power Requirements:	115 VAC, 6 amp, 50/60 Hz, 230 VAC, 3 amp, 50/60 Hz
Dimensions:	17" W x 17-1/4" H x 21-5/8" D (Add an additional 2-1/2" to the depth for cables at back of unit)
Weight:	50 lbs.
Operating Temperature Range:	10° to 45° C (50° to 113° F)
Storage Temperature Range:	-35° to 60° C (-35° to 140° F)

### Total Solutions

Hardware  
Software  
Installation  
Service

Diebold, Incorporated  
Post Office Box 3077  
Dept. 9-B-16  
North Canton, Ohio  
44720-9077

800.999.3600 USA  
330.490.4000 International  
330.489.4272 Fax  
[www.diebold.com](http://www.diebold.com)

©Diebold, Incorporated, 2008. All rights reserved.  
Litho in USA. File No. 70-571